



2X3P~2X12P

2X2P

2X1P

MATERIALS

1. HOUSING : NYLON 66 UL 94V-2, BLACK
1. CURRENT RATE: 5A AC,DC
2. VOLTAGE RATE: 250V AC,DC
3. TEMPERATUR RANGE: -25°C~+85°C
4. CONTACT RESISTANCE: 10m OHMS MAX
5. INSULATION RESISTANCE: 1000M ohms MIN
6. WITHSTAND VOLTAGE: 1500V AC/ MINUTE

SPECIFICATION

PART NUMBER

CTP - 04KA - 2 X X - 0 1 0

SERIES

TWO ROWS

NUMBER PER ROW
(1~12)

Number Of Position	Dimensions		Number Of Position	Dimensions	
	A	B		A	B
2	—	3.80	14	18.00	21.80
4	3.00	6.80	16	21.00	24.80
6	6.00	9.80	18	24.00	27.80
8	9.00	12.80	20	27.00	30.80
10	12.00	15.80	22	30.00	33.80
12	15.00	18.80	24	33.00	36.80

REV.	DATE	RELEASE DESCRIPTION
A	0715,2005	

Connect-Tech Products Corp. TEL:+1 510 4400578 www.Connect-Tech-Products.com		HOUSING SERIES MICROFTT 3.0mm PITCH MICRO FTT	
TOLERANCES X.X ±0.3 X.XX ±0.2 X.XXX ±0.1 Angle ±5°		DRAWN BY <i>Lion</i>	CHECKED BY <i>J.Y.H</i>
APPROVED BY <i>Omar</i>		UNIT MM	SCALE NONE
SIZE A4	DRAW NO. D004-KA010	REV. A	REV. A